

# Material Safety Data Sheet



## Hazardous Substance, NON-Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

#### Product name: **Bostik Ultraseal Polyurethane Wet Area Membrane**

**Synonyms:**

Bostik Ultraseal Polyurethane Wet Area Membrane, 600 mL  
Bostik Ultraseal Polyurethane Wet Area Membrane, 15 Litres

**Mancode**

230227  
242314

**Recommended use:** 1 part moisture curing flexible waterproofing membrane.

**Supplier:** Bostik Australia Pty Ltd

**ABN:** 79 003 893 838

**Street Address:** 51-71 High Street  
Thomastown VIC 3074  
Australia

**Telephone:** +613 9279-9333

**Facsimile:** +613 9279-9342

**Emergency telephone number:** 1800 033 111

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of NOHSC Australia.

**Hazard Category:**

Xn Harmful

**Risk Phrase(s):**

R20: Harmful by inhalation.

R42: May cause sensitisation by inhalation.

**Safety Phrase(s):**

S23: Do not breathe vapour.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

**Poisons Schedule (Aust):** Not applicable

### 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Toluene di-isocyanate	584-84-9	<1%
Non hazardous ingredients	-	Balance
		100%

**Product name:** Bostik Ultraseal Polyurethane Wet Area Membrane

**Substance Key:** BOS0029302

**Issued:** 23 February 2006

**Version:** 1.1

**Page:** 1 of 6

# Material Safety Data Sheet



## 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

**Skin contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**Notes to physician:** Treat symptomatically. Effects may be delayed.

## 5. FIRE-FIGHTING MEASURES

**Specific hazards:** Combustible material.

**Fire fighting further advice:** On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

**Hazchem Code:** Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

### LARGE SPILLS

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

**Dangerous Goods – Initial Emergency Response Guide No:** Not applicable.

# Material Safety Data Sheet



## 7. HANDLING AND STORAGE

**Handling:** Avoid skin and eye contact and inhalation of vapour.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

However for:

	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	CARCINOGEN CATEGORY	NOTICES
Isocyanates, all (as -NCO)	-	0.02	-	0.07	-	Sen

As published by the National Occupational Health & Safety Commission (NOHSC Australia).

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sen' notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

\*\*\* Medical supervision of all employees who handle or come in contact with respiratory sensitisers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products.\*\*\*

\*\*\* The Occupation Exposure Standards do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further exposure.\*\*\*

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the following ingredients in this material requires Health Surveillance:

Isocyanates.

For detailed information see "Guidelines for Health Surveillance [NOHSC: 7039 (1995)]"

# Material Safety Data Sheet



**Engineering measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Keep containers closed when not in use.

**Personal protection equipment:** OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from polyvinyl alcohol (PVA) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form / Colour / Odour:** Non flowing yellow thixotropic paste with solvent odour.

<b>Solubility:</b>	Insoluble in water.
<b>Specific Gravity (20 °C):</b>	1.33
<b>Relative Vapour Density (air=1):</b>	>1
<b>Vapour Pressure (20 °C):</b>	N Av
<b>Flash Point (°C):</b>	N Av
<b>Flammability Limits (%):</b>	N Av
<b>Autoignition Temperature (°C):</b>	N Av
<b>Melting Point/Range (°C):</b>	N Av
<b>Boiling Point/Range (°C):</b>	N Av
<b>pH:</b>	N App

(Typical values only - consult specification sheet)  
N Av = Not available      N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Avoid high temperatures

**Incompatible Materials:** Water, alcohols, amines, acids and bases

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes - may include isocyanates.

**Hazardous reactions:** Will react exothermically with water and all organic compounds containing active hydrogen groups.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Product name:** Bostik Ultraseal Polyurethane Wet Area Membrane

**Substance Key:** BOS0029302

**Issued:** 23 February 2006

**Version:** 1.1

**Page:** 4 of 6

# Material Safety Data Sheet



## Acute Effects

**Inhalation:** Vapour is harmful. A respiratory sensitisier. Can cause possible allergic reactions.

**Skin contact:** Contact with skin may result in irritation.

**Eye contact:** May be an eye irritant.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Long Term Effects:** No information available for product.

## Acute toxicity / Chronic toxicity

No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

### MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. REGULATORY INFORMATION

**Poisons Schedule (Aust):** Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

# Material Safety Data Sheet



## 16. OTHER INFORMATION

### Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of its client.

Reason(s) For Issue: Correction to Mancode Number

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.